

**Product Sizes:** (other rail sizes available)

We currently stock the 1.5' rail in sizes that range up to 12 ft. long

- 17" to 27" range
- 22" to 36" range
- 28" to 46" range
- 34" to 55" range
- 40" to 64" range
- 52" to 88" range

**Longer Lengths with Universal Hydraulic Extension**

- By adding a 56" universal hydraulic extension, we can offer longer lengths
- 84" to 102" (using the 28" to 46" shore jacks with 56" extensions)
- 90" to 111" (using the 34" to 55" shore jacks with 56" extensions)
- 108" to 144" (using the 52" to 88" shore jacks with 56" extensions)

**Plastic Pump**

- Offers a wider base so pump is less likely to tip over and spill shoring fluid in back of the vehicle
- Plastic design helps with many years of life with eliminating possibility of bottom rusting out when using a metal bucket pump.

**Metal Pump**

- Lower initial cost
- The only disadvantages are that the pump can more easily tip over getting oil in the back of the transport vehicle
- There is a possibility over time that the bottom of the pump can could start rusting

**Removal Hook & Release Tools**

- Used for installing the vertical hydraulic shores prior to entering the trench & also used to remove the vertical hydraulic shores at end of use
  - 48" long, 60" long or 84" long tools

**Finn Form Boards**

- Used in conjunction with vertical hydraulic shoring
  - 4' x 4' sizes
  - 4' x 8' sizes

## **Hydraulic Shoring Fluid**

- Summer Grade
- Winter Grade
  - (Sewer Sammy Tip) Use Winter Grade shoring fluid throughout the year. Then you do not have to worry about forgetting to change out the fluid to winter fluid when the cold temperatures set in.